



# TB515

## RADIAL OFF-THE-ROAD TIRES

**Suitable for high-speed performance.**  
**With super heat dispersion.**  
**With a wearable tread.**  
**With perfect puncture resistance.**  
**Excellent cushion for the operator.**  
**Low fuel consumption.**

Size	Code	Star rating	Load Index	Standard Rim	inflated （mm）				Max.Load (kg)	Standard Pressure(bar)	Max.Speed (km/h)	Tubeless	Tread depth
					Overall diameter±3%		Section Width	+6%  -3%					
					Normal pattern	super pattern							
					Normal pattern	Deeper Pattern							
20.5R25	G-2	☆☆	193/177	17.00/2.0	1493	1548	521	11500/7300	6.5/5.25	10/50	TL	29	
	L-2	☆	186/161/168					9500/4625/5600	5.0/3.0/3.75	10/40/50			
		☆☆	193/177					11500/7300	6.5/5.25	10/50			
17.5R25	G-2	☆	176/153/157	14.00/1.5	1348	1399	445	7100/3650/4125	5.0/3.0/3.75	10/40/50	TL	26	
		☆☆	182/167					8500/5450	6.5/5.25	10/50			
	L-2	☆	176/153/157					7100/3650/4125	5.0/3.0/3.75	10/40/50			
		☆☆	182/167					8500/5450	6.5/5.25	10/50			
Note: load index,Max load(kg),the figure between left and right of slant is accordance with that of standard pressure(bar) and Max speed(km/h).													

Suitable for high-speed performance.

With super heat dispersion. Low fuel consumption.

With a wearable tread. Excellent cushion for the operator.

With perfect puncture resistance.